

# PX8000 400V 50HZ #AVR

ENGINEERED FOR PROFESSIONAL PERFORMANCE



Ready to move where power is needed, and configured with a strong and compact frame with integrated handle and wheels, that allow to transport it easily.

## Caracteristici principale

Frecvență	Hz	50
Tensiune	V	400
Factor de putere	cos $\phi$	0.8
Faze		3

## Regim De Putere

Putere pasivă LTP	kVA	6.0
Putere pasivă LTP	kW	4.8
Putere continuă COP	kVA	5.0
Putere continuă COP	kW	4.0

## Putere Monofazica Nominala

Putere pasivă monofazică LTP	kVA	2.0
Putere continuă monofazică COP	kVA	1.5

Ratings definition (According to standard ISO8528 1:2005)

### Date tehnice motor

Producător motor		PRAMAC
Model piesă		SR190F
Sistem de răcire motor		Aer
Deplasament	cm <sup>3</sup>	420
Aspirație		Natural
Viteză nominală de funcționare	rpm	3000
Regulator de viteză		Mecanic
Combustibil		Benzină
Capacitate ulei	l	1.1
Sistem de pornire		ELECTRICĂ

### Date tehnice alternator

Clasă		F
Clasificare protecție infiltrare		23/44
Borne		2
Frecvență	Hz	50
Sistem de regulare tensiune		AVR

### Date dimensionale

Lungime	(L) mm	727
Lățime	(W) mm	515
Înălțime	(H) mm	670
Greutate fără combustibil	Kg	97
Capacitate rezervor combustibil	l	27

### Autonomie

Consum combustibil la 75% PRP	l/h	2.06
Consum combustibil la 100% PRP	l/h	2.75
Timp de funcționare la @ 75% PRP	h	13.11
Timp de funcționare la @ 100% PRP	h	9.82

### Nivel zgomot

Nivelul de zgomot garantat (LWA)	dBA	97
Nivel de stridență a zgomotului la 7 mt	dB(A)	69



## PANOURI DE CONTROL GENSET

Montat pe genset și conținând: instrumentație, control, protecție a setului generator și prize.

### COMENZI:

- Porniți comutatorul OFF - ON

### INSTRUMENTAȚIE

- Voltmetru
- Contor orar
- Aparat de măsurare a frecvenței
- Indicator al nivelului de combustibil

### PROTECȚII:

- Ruptor circuit termal
- Protector ulei

### PRIZE

SCHUKO 230V 16A IP54	1
2P+T CEE 230V 16A IP44	1
3P+N+T CEE 400V 16A IP44	1



The information is aligned with the Data file at the time of download. Printed on 30/12/2019 (ID 2318)

©2019 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

